

The Kokkos Lectures

Module 1: Introduction, Building and Parallel Dispatch

July 28, 2026

Kokkos is C++ Performance Portability

- ▶ Write a *single source* implementation using C++
- ▶ Use a *descriptive* Programming Model
- ▶ Compile for GPUs and CPUs

Kokkos is Ready for Use

- ▶ Well established project since 2012
- ▶ Part of the Linux Foundation's HPSF
- ▶ Major buy-in by US DOE National Labs and the French CEA
- ▶ Well over 300 projects with over 1500 developers use Kokkos
- ▶ Robust support for software stacks: GCC 11+, Clang 14+, NVCC 12+, ROCM 6.2, Intel 2022+, MSVC

Online Resources:

- ▶ <https://github.com/kokkos>:
 - ▶ Primary Kokkos GitHub Organization
- ▶ <https://kokkos.org/kokkos-tutorials/>:
 - ▶ Built tutorial slides
- ▶ <https://kokkos.org>:
 - ▶ Project website including API reference
- ▶ <https://kokkosteam.slack.com>:
 - ▶ Ask questions in the #kokkos-tutorial channel.
 - ▶ Ask an existing workspace member for an invitation.

- ▶ Module 1: Introduction, Building and Parallel Dispatch
- ▶ Module 2: Views and Spaces
- ▶ Module 3: Data Structures + MultiDimensional Loops
- ▶ Module 4: Hierarchical Parallelism
- ▶ Module 5: Tasking, Streams and SIMD
- ▶ Module 6: Internode: MPI and PGAS
- ▶ Module 7: Tools: Profiling, Tuning and Debugging
- ▶ Module 8: Kernels: Sparse and Dense Linear Algebra
- ▶ Module 9: Fortran inter-op

Lectures

- ▶ Typically 90 minutes of lecture
- ▶ Submodules have associated exercise as homework
- ▶ Typically 2-3 Exercises per lecture
- ▶ Exercises will be talked through at next meeting.

Exercises

- ▶ Exercises are small codes with places to do modifications.
- ▶ Access to GPUs helpful for most of them, but most can be done on pure CPU systems.
- ▶ Only dependent on standard compilers (e.g. Clang, NVCC)
- ▶ Ongoing support at <https://kokkosteam.slack.com>

Introduction

What is Kokkos? Who is behind it? Why should you use it?

Parallel Dispatch

Pattern, Policy and Body: how to parallelize simple code with Kokkos.

Building

What do you need to build Kokkos and Apps? How to integrate into your build system?

Introduction

Learning objectives:

- ▶ Why do we need Kokkos
- ▶ The Kokkos Ecosystem
- ▶ The Kokkos Team

Current Generation: Programming Models OpenMP 3, CUDA and OpenACC depending on machine



LANL/SNL Trinity
Intel Haswell / Intel KNL
OpenMP 3




LLNL SIERRA
IBM Power9 / NVIDIA Volta
CUDA / OpenMP^(a)



ORNL Summit
IBM Power9 / NVIDIA Volta
CUDA / OpenACC / OpenMP^(a)



SNL Astra
ARM CPUs
OpenMP 3



Riken Fugaku
ARM CPUs with SVE
OpenMP 3 / OpenACC^(b)

Upcoming Generation: Programming Models OpenMP 5, CUDA, HIP and DPC++ depending on machine



NERSC Perlmutter
AMD CPU / NVIDIA GPU
CUDA / OpenMP 5^(c)



ORNL Frontier
AMD CPU / AMD GPU
HIP / OpenMP 5^(d)



ANL Aurora
Xeon CPUs / Intel GPUs
DPC++ / OpenMP 5^(e)



LLNL El Capitan
AMD CPU / AMD GPU
HIP / OpenMP 5^(d)

(a) Initially not working. Now more robust for Fortran than C++, but getting better.

(b) Research effort.

(c) OpenMP 5 by NVIDIA.

(d) OpenMP 5 by HPE.

(e) OpenMP 5 by Intel.

Industry Estimate

A full time software engineer writes 10 lines of production code per hour: 20k LOC/year.

- ▶ Typical HPC production app: 300k-600k lines
 - ▶ Sandia alone maintains a few dozen
- ▶ Large Scientific Libraries:
 - ▶ E3SM: 1,000k lines
 - ▶ Trilinos: 4,000k lines

Conservative estimate: need to rewrite 10% of an app to switch Programming Model

Industry Estimate

A full time software engineer writes 10 lines of production code per hour: 20k LOC/year.


- ▶ Typical HPC production app: 300k-600k lines
 - ▶ Sandia alone maintains a few dozen
- ▶ Large Scientific Libraries:
 - ▶ E3SM: 1,000k lines
 - ▶ Trilinos: 4,000k lines


Conservative estimate: need to rewrite 10% of an app to switch Programming Model

Software Cost Switching Vendors

Just switching Programming Models costs multiple person-years per app!

- ▶ A C++ Programming Model for Performance Portability
 - ▶ Implemented as a template library on top CUDA, HIP, OpenMP, ...
 - ▶ Aims to be descriptive not prescriptive
 - ▶ Aligns with developments in the C++ standard
- ▶ Expanding solution for common needs of modern science and engineering codes
 - ▶ Math libraries based on Kokkos
 - ▶ Tools for debugging, profiling and tuning
 - ▶ Utilities for integration with Fortran and Python
- ▶ It is an Open Source project with a growing community
 - ▶ Maintained and developed at <https://github.com/kokkos>
 - ▶ Hundreds of users at many large institutions






Primary
Teams



Support
Efforts



Kokkos helps improve ISO C++



Ten current or former Kokkos team members are members of the ISO C++ standard committee.

C++11 std::atomic insufficient for HPC

- ▶ Objects, not functions, with only atomic access
- ▶ Can't use non-atomic access in one operation, and then atomic access in the next

C++20 std::atomic_ref adds atomic capabilities as in Kokkos

- ▶ Can wrap standard allocations.
- ▶ Works also for sizes which can't be done lock-free (e.g. `complex<double>`)
- ▶ Atomic operations on reasonably arbitrary types

```
// Kokkos today
Kokkos::atomic_add(&a[i], 5.0);

// atomic_ref in ISO C\texttt{++}20
std::atomic_ref(a[i]) += 5.0;
```

C++ does not provide multi dimensional arrays

- ▶ Every scientific programming language has them: Fortran, Matlab, Python, ...

C++23 std::mdspan adds Kokkos::View like arrays

- ▶ Reference semantics.
- ▶ Compile time and runtime extents (also mixed)
- ▶ Data layouts to allow for adapting hardware specific access patterns.
- ▶ Subviews!

```
// Kokkos today
View<float**[5],LayoutLeft> a("A",10,12); a(3,5,1) = 5;

// mdspan in ISO C\texttt{++}23
using ext = extents<int,dynamic_extent,dynamic_extent,5>;
mdspan<float,ext,layout_left> a(ptr,10,12); a[3,5,1]+=5;
```

Knowledge of C++: class constructors, member variables, member functions, member operators, template arguments

Using your own `${HOME}`

- ▶ Git
- ▶ CMake 3.16 (or newer)
- ▶ GCC 8.2 (or newer) *OR* Clang 8.0 (or newer)
- ▶ CUDA nvcc 11.0 (or newer) *AND* NVIDIA compute capability 6.0 (or newer)
- ▶ git clone <https://github.com/kokkos/kokkos-tutorials>
into `${HOME}/Kokkos/kokkos-tutorials`

Slides are in

`${HOME}/Kokkos/kokkos-tutorials/LectureSeries`

Exercises are in

`${HOME}/Kokkos/kokkos-tutorials/Exercises`

Online Resources:

- ▶ <https://kokkos.org>: Project website with documentation
- ▶ <https://github.com/kokkos>: GitHub organization
- ▶ <https://github.com/kokkos/kokkos-tutorials>: Tutorial exercises
- ▶ <https://kokkosteam.slack.com>: Slack channel for Kokkos

Kokkos' basic capabilities:

- ▶ Simple 1D data parallel computational patterns
- ▶ Deciding where code is run and where data is placed
- ▶ Managing data access patterns for performance portability
- ▶ Multidimensional data parallelism

Kokkos' advanced capabilities:

- ▶ Thread safety, thread scalability, and atomic operations
- ▶ Hierarchical patterns for maximizing parallelism
- ▶ Task based programming with Kokkos

Kokkos' tools and Kernels:

- ▶ How to profile, tune and debug Kokkos code
- ▶ Interacting with Python and Fortran
- ▶ Using Kokkos Kernels math library

- ▶ Kokkos enables **Single Source Performance Portable Codes**
- ▶ **Simple things stay simple** - it is not much more complicated than OpenMP
- ▶ **Advanced performance optimizing capabilities** easier to use with Kokkos than e.g. CUDA or HIP
- ▶ Kokkos provides data abstractions critical for performance portability not available in other programming models
Controlling data access patterns is key for obtaining performance
- ▶ The **Kokkos Ecosystem** comes with tools (profiling, debugging, tuning, math libraries, etc.) needed for application development in professional settings


Assume you are here because:

- ▶ Want to use **all** HPC node architectures; including GPUs
- ▶ Are familiar with **C++**
- ▶ Want GPU programming to be **easier**
- ▶ Would like **portability**, as long as it doesn't hurt performance

Helpful for understanding nuances:

- ▶ Are familiar with **data parallelism**
- ▶ Are familiar with **OpenMP**
- ▶ Are familiar with **GPU architecture** and **CUDA**

Target machine:



Important Point

There's a difference between *portability* and *performance portability*.

Example: implementations may target particular architectures and may not be *thread scalable*.
(e.g., locks on CPU won't scale to 100,000 threads on GPU)

Important Point

There's a difference between *portability* and *performance portability*.

Example: implementations may target particular architectures and may not be *thread scalable*.

(e.g., locks on CPU won't scale to 100,000 threads on GPU)

Goal: write **one implementation** which:

- ▶ compiles and **runs on multiple architectures**,
- ▶ obtains **performant memory access patterns** across architectures,
- ▶ can leverage **architecture-specific features** where possible.

Important Point

There's a difference between *portability* and *performance portability*.

Example: implementations may target particular architectures and may not be *thread scalable*.

(e.g., locks on CPU won't scale to 100,000 threads on GPU)

Goal: write **one implementation** which:

- ▶ compiles and **runs on multiple architectures**,
- ▶ obtains **performant memory access patterns** across architectures,
- ▶ can leverage **architecture-specific features** where possible.

Kokkos: performance portability across manycore architectures.

Concepts for Data Parallelism

Learning objectives:

- ▶ Terminology of pattern, policy, and body.
- ▶ The data layout problem.

```
for (element = 0; element < numElements; ++element) {  
    total = 0;  
    for (qp = 0; qp < numQPs; ++qp) {  
        total += dot(left[element][qp], right[element][qp]);  
    }  
    elementValues[element] = total;  
}
```

Pattern

Policy

Body

```
for (element = 0; element < numElements; ++element) {  
    total = 0;  
    for (qp = 0; qp < numQPs; ++qp) {  
        total += dot(left[element][qp], right[element][qp]);  
    }  
    elementValues[element] = total;  
}
```

Terminology:

- ▶ **Pattern:** structure of the computations
for, reduction, scan, task-graph, ...
- ▶ **Execution Policy:** how computations are executed
static scheduling, dynamic scheduling, thread teams, ...
- ▶ **Computational Body:** code which performs each unit of
work; e.g., the loop body

⇒ The **pattern** and **policy** drive the computational **body**.

What if we want to **thread** the loop?

```
for (element = 0; element < numElements; ++element) {  
    total = 0;  
    for (qp = 0; qp < numQPs; ++qp) {  
        total += dot(left[element][qp], right[element][qp]);  
    }  
    elementValues[element] = total;  
}
```

What if we want to **thread** the loop?

```
#pragma omp parallel for
for (element = 0; element < numElements; ++element) {
    total = 0;
    for (qp = 0; qp < numQPs; ++qp) {
        total += dot(left[element][qp], right[element][qp]);
    }
    elementValues[element] = total;
}
```

(Change the *execution policy* from “serial” to “parallel.”)

What if we want to **thread** the loop?

```
#pragma omp parallel for
for (element = 0; element < numElements; ++element) {
    total = 0;
    for (qp = 0; qp < numQPs; ++qp) {
        total += dot(left[element][qp], right[element][qp]);
    }
    elementValues[element] = total;
}
```

(Change the *execution policy* from “serial” to “parallel.”)

OpenMP is simple for parallelizing loops on multi-core CPUs,
but what if we then want to do this on **other architectures**?

Intel PHI *and* NVIDIA GPU *and* AMD GPU *and* ...

Option 1: OpenMP 4.5

```
#pragma omp target data map(...)
#pragma omp teams num_teams(...) num_threads(...) private(...)
#pragma omp distribute
for (element = 0; element < numElements; ++element) {
    total = 0
    #pragma omp parallel for
        for (qp = 0; qp < numQPs; ++qp)
            total += dot(left[element][qp], right[element][qp]);
    elementValues[element] = total;
}
```

Option 1: OpenMP 4.5

```
#pragma omp target data map(...)
#pragma omp teams num_teams(...) num_threads(...) private(...)
#pragma omp distribute
for (element = 0; element < numElements; ++element) {
    total = 0
    #pragma omp parallel for
    for (qp = 0; qp < numQPs; ++qp)
        total += dot(left[element][qp], right[element][qp]);
    elementValues[element] = total;
}
```

Option 2: OpenACC

```
#pragma acc parallel copy(...) num_gangs(...) vector_length(...)
#pragma acc loop gang vector
for (element = 0; element < numElements; ++element) {
    total = 0;
    for (qp = 0; qp < numQPs; ++qp)
        total += dot(left[element][qp], right[element][qp]);
    elementValues[element] = total;
}
```

A standard thread parallel programming model
may give you portable parallel execution
if it is supported on the target architecture.

But what about performance?

A standard thread parallel programming model *may* give you portable parallel execution *if* it is supported on the target architecture.

But what about performance?

Performance depends upon the computation's **memory access pattern**.

```
#pragma something, opencl, etc.  
for (element = 0; element < numElements; ++element) {  
    total = 0;  
    for (qp = 0; qp < numQPs; ++qp) {  
        for (i = 0; i < vectorSize; ++i) {  
            total +=  
                left[element * numQPs * vectorSize +  
                    qp * vectorSize + i] *  
                right[element * numQPs * vectorSize +  
                    qp * vectorSize + i];  
        }  
    }  
    elementValues[element] = total;  
}
```

```
#pragma something, opencl, etc.  
for (element = 0; element < numElements; ++element) {  
    total = 0;  
    for (qp = 0; qp < numQPs; ++qp) {  
        for (i = 0; i < vectorSize; ++i) {  
            total +=  
                left[element * numQPs * vectorSize +  
                    qp * vectorSize + i] *  
                right[element * numQPs * vectorSize +  
                    qp * vectorSize + i];  
        }  
    }  
    elementValues[element] = total;  
}
```

Memory access pattern problem: CPU data layout reduces GPU performance by more than 10X.

```
#pragma something, opencl, etc.  
for (element = 0; element < numElements; ++element) {  
    total = 0;  
    for (qp = 0; qp < numQPs; ++qp) {  
        for (i = 0; i < vectorSize; ++i) {  
            total +=  
                left[element * numQPs * vectorSize +  
                    qp * vectorSize + i] *  
                right[element * numQPs * vectorSize +  
                    qp * vectorSize + i];  
        }  
    }  
    elementValues[element] = total;  
}
```

Memory access pattern problem: CPU data layout reduces GPU performance by more than 10X.

Important Point

For performance the memory access pattern *must* depend on the architecture.

How does Kokkos address performance portability?

Kokkos is a *productive, portable, performant*, shared-memory programming model.

- ▶ is a C++ **library**, not a new language or language extension.
- ▶ provides **clear, concise, scalable** parallel patterns.
- ▶ lets you write algorithms once and run on **many architectures**
e.g. multi-core CPU, GPUs, Xeon Phi, ...
- ▶ **minimizes** the amount of architecture-specific **implementation details** users must know.
- ▶ *solves the data layout problem* by using multi-dimensional arrays with architecture-dependent **layouts**

Data parallel patterns

Learning objectives:

- ▶ How computational bodies are passed to the Kokkos runtime.
- ▶ How work is mapped to execution resources.
- ▶ The difference between `parallel_for` and `parallel_reduce`.
- ▶ Start parallelizing a simple example.

Data parallel patterns and work

```
for (atomIndex = 0; atomIndex < numberOfAtoms; ++atomIndex) {  
    atomForces[atomIndex] = calculateForce(...data...);  
}
```

Kokkos maps **work** to execution resources

Data parallel patterns and work

```
for (atomIndex = 0; atomIndex < numberOfAtoms; ++atomIndex) {  
    atomForces[atomIndex] = calculateForce(...data...);  
}
```

Kokkos maps **work** to execution resources

- ▶ each iteration of a computational body is a **unit of work**.
- ▶ an **iteration index** identifies a particular unit of work.
- ▶ an **iteration range** identifies a total amount of work.

Data parallel patterns and work

```
for (atomIndex = 0; atomIndex < numberOfAtoms; ++atomIndex) {  
    atomForces[atomIndex] = calculateForce(...data...);  
}
```

Kokkos maps **work** to execution resources

- ▶ each iteration of a computational body is a **unit of work**.
- ▶ an **iteration index** identifies a particular unit of work.
- ▶ an **iteration range** identifies a total amount of work.

Important concept: Work mapping

You give an **iteration range** and **computational body** (kernel) to Kokkos, and Kokkos decides how to map that work to execution resources.

How are computational bodies given to Kokkos?

How are computational bodies given to Kokkos?

As **functors** or *function objects*, a common pattern in C++.

How are computational bodies given to Kokkos?

As **functors** or *function objects*, a common pattern in C++.

Quick review, a **functor** is a function with data. Example:

```
struct ParallelFunctor {  
    ...  
    void operator()( a work assignment ) const {  
        /* ... computational body ... */  
    ...  
};
```

How is work assigned to functor operators?

How is work assigned to functor operators?

A total amount of work items is given to a Kokkos pattern,

```
ParallelFunctor functor;  
Kokkos::parallel_for(numberOfIterations, functor);
```

How is work assigned to functor operators?

A total amount of work items is given to a Kokkos pattern,

```
ParallelFunctor functor;  
Kokkos::parallel_for(numberOfIterations, functor);
```

and work items are assigned to functors one-by-one:

```
struct Functor {  
    void operator()(const int64_t index) const {...}  
}
```

How is work assigned to functor operators?

A total amount of work items is given to a Kokkos pattern,

```
ParallelFunctor functor;  
Kokkos::parallel_for(numberOfIterations, functor);
```

and work items are assigned to functors one-by-one:

```
struct Functor {  
    void operator()(const int64_t index) const {...}  
}
```

Warning: concurrency and order

Concurrency and ordering of parallel iterations is *not* guaranteed by the Kokkos runtime.

How is data passed to computational bodies?

```
for (atomIndex = 0; atomIndex < numberOfAtoms; ++atomIndex) {  
    atomForces[atomIndex] = calculateForce(...data...);  
}
```

```
struct AtomForceFunctor {  
    ...  
    void operator()(const int64_t atomIndex) const {  
        atomForces[atomIndex] = calculateForce(...data...);  
    }  
    ...  
}
```

How is data passed to computational bodies?

```
for (atomIndex = 0; atomIndex < numberOfAtoms; ++atomIndex) {  
    atomForces[atomIndex] = calculateForce(...data...);  
}
```

```
struct AtomForceFunctor {  
    ...  
    void operator()(const int64_t atomIndex) const {  
        atomForces[atomIndex] = calculateForce(...data...);  
    }  
    ...  
}
```

How does the body access the data?

Important concept

A parallel functor body must have access to all the data it needs through the functor's **data members**.

Putting it all together: the complete functor:

```
struct AtomForceFunctor {  
    ForceType _atomForces;  
    DataType _atomData;  
    AtomForceFunctor(/* args */) {...}  
    void operator()(const int64_t atomIndex) const {  
        _atomForces[atomIndex] = calculateForce(_atomData);  
    }  
};
```

Putting it all together: the complete functor:

```
struct AtomForceFunctor {  
    ForceType _atomForces;  
    DataType _atomData;  
    AtomForceFunctor(/* args */) {...}  
    void operator()(const int64_t atomIndex) const {  
        _atomForces[atomIndex] = calculateForce(_atomData);  
    }  
};
```

Q/ How would we **reproduce serial execution** with this functor?

Serial

```
for (atomIndex = 0; atomIndex < numberOfAtoms; ++atomIndex){  
    atomForces[atomIndex] = calculateForce(data);  
}
```

Putting it all together: the complete functor:

```

struct AtomForceFunctor {
    ForceType _atomForces;
    DataType _atomData;
    AtomForceFunctor(/* args */) {...}
    void operator()(const int64_t atomIndex) const {
        _atomForces[atomIndex] = calculateForce(_atomData);
    }
};

```

Q/ How would we **reproduce serial execution** with this functor?

Serial

```

for (atomIndex = 0; atomIndex < numberOfAtoms; ++atomIndex){
    atomForces[atomIndex] = calculateForce(data);
}

```

Functor

```

AtomForceFunctor functor(atomForces, data);
for (atomIndex = 0; atomIndex < numberOfAtoms; ++atomIndex){
    functor(atomIndex);
}

```

The complete picture (using functors):

1. Defining the functor (operator+data):

```
struct AtomForceFunctor {  
    ForceType _atomForces;  
    DataType _atomData;  
  
    AtomForceFunctor(ForceType atomForces, DataType data) :  
        _atomForces(atomForces), _atomData(data) {}  
  
    void operator()(const int64_t atomIndex) const {  
        _atomForces[atomIndex] = calculateForce(_atomData);  
    }  
}
```

2. Executing in parallel with Kokkos pattern:

```
AtomForceFunctor functor(atomForces, data);  
Kokkos::parallel_for(numberOfAtoms, functor);
```

Functors are tedious $\Rightarrow$ **C++11 Lambdas** are concise

```
atomForces already exists  
data already exists  
Kokkos::parallel_for(numberOfAtoms,  
    [=] (const int64_t atomIndex) {  
        atomForces[atomIndex] = calculateForce(data);  
    }  
);
```

Functors are tedious $\Rightarrow$ **C++11 Lambdas** are concise

```
atomForces already exists  
data already exists  
Kokkos::parallel_for(numberOfAtoms,  
    [=] (const int64_t atomIndex) {  
        atomForces[atomIndex] = calculateForce(data);  
    }  
);
```

A lambda is not *magic*, it is the compiler **auto-generating** a **functor** for you.

Functors are tedious $\Rightarrow$ **C++11 Lambdas** are concise

```
atomForces already exists  
data already exists  
Kokkos::parallel_for(numberOfAtoms,  
    [=] (const int64_t atomIndex) {  
        atomForces[atomIndex] = calculateForce(data);  
    }  
);
```

A lambda is not *magic*, it is the compiler **auto-generating** a **functor** for you.

Warning: Lambda capture and C++ containers

For portability to GPU a lambda must capture by value [=].
Don't capture containers (e.g., `std::vector`) by value because it will copy the container's entire contents.

How does this compare to OpenMP?

Serial

```
for (int64_t i = 0; i < N; ++i) {  
    /* loop body */  
}
```

OpenMP

```
#pragma omp parallel for  
for (int64_t i = 0; i < N; ++i) {  
    /* loop body */  
}
```

Kokkos


```
parallel_for(N, [=] (const int64_t i) {  
    /* loop body */  
});
```

Important concept

Simple Kokkos usage is **no more conceptually difficult** than OpenMP, the annotations just go in different places.


Riemann-sum-style numerical integration:

$$y = \int_{\text{lower}}^{\text{upper}} \text{function}(x) dx$$



Riemann-sum-style numerical integration:


$$y = \int_{\text{lower}}^{\text{upper}} \text{function}(x) dx$$



```
double totalIntegral = 0;
for (int64_t i = 0; i < numberOfIntervals; ++i) {
    const double x =
        lower + (i/numberOfIntervals) * (upper - lower);
    const double thisIntervalsContribution = function(x);
    totalIntegral += thisIntervalsContribution;
}
totalIntegral *= dx;
```

Riemann-sum-style numerical integration:

$$y = \int_{\text{lower}}^{\text{upper}} \text{function}(x) dx$$




```
double totalIntegral = 0;
for (int64_t i = 0; i < numberOfIntervals; ++i) {
    const double x =
        lower + (i/numberOfIntervals) * (upper - lower);
    const double thisIntervalsContribution = function(x);
    totalIntegral += thisIntervalsContribution;
}
totalIntegral *= dx;
```

How do we **parallelize** it? *Correctly?*

Riemann-sum-style numerical integration:

$$y = \int_{\text{lower}}^{\text{upper}} \text{function}(x) dx$$



Pattern?

```
double totalIntegral = 0;
for (int64_t i = 0; i < numberOfIntervals; ++i) {
    const double x =
        lower + (i/numberOfIntervals) * (upper - lower);
    const double thisIntervalsContribution = function(x);
    totalIntegral += thisIntervalsContribution;
}
totalIntegral *= dx;
```

Body?

Policy?

How do we **parallelize** it? *Correctly?*

An (incorrect) attempt:

```
double totalIntegral = 0;
Kokkos::parallel_for(numberOfIntervals,
    [=] (const int64_t index) {
        const double x =
            lower + (index/numberOfIntervals) * (upper - lower);
        totalIntegral += function(x);}
);
totalIntegral *= dx;
```

First problem: compiler error; cannot increment totalIntegral (lambdas capture by value and are treated as const!)

An (incorrect) solution to the (incorrect) attempt:

```
double totalIntegral = 0;
double * totalIntegralPointer = &totalIntegral;
Kokkos::parallel_for(numberOfIntervals,
    [=] (const int64_t index) {
        const double x =
            lower + (index/numberOfIntervals) * (upper - lower);
        *totalIntegralPointer += function(x);}
    );
totalIntegral *= dx;
```

An (incorrect) solution to the (incorrect) attempt:

```
double totalIntegral = 0;
double * totalIntegralPointer = &totalIntegral;
Kokkos::parallel_for(numberOfIntervals,
    [=] (const int64_t index) {
        const double x =
            lower + (index/numberOfIntervals) * (upper - lower);
        *totalIntegralPointer += function(x);}
    );
totalIntegral *= dx;
```

Second problem: race condition

step	thread 0	thread 1
0	load	
1	increment	load
2	write	increment
3		write

Root problem: we're using the **wrong pattern**, *for* instead of *reduction*

Root problem: we're using the **wrong pattern**, *for* instead of *reduction*

Important concept: Reduction

Reductions combine the results contributed by parallel work.

Root problem: we're using the **wrong pattern**, *for* instead of *reduction*

Important concept: Reduction

Reductions combine the results contributed by parallel work.

How would we do this with **OpenMP**?

```
double finalReducedValue = 0;
#pragma omp parallel for reduction(+:finalReducedValue)
for (int64_t i = 0; i < N; ++i) {
    finalReducedValue += ...
}
```

Root problem: we're using the **wrong pattern**, *for* instead of *reduction*

Important concept: Reduction

Reductions combine the results contributed by parallel work.

How would we do this with **OpenMP**?

```
double finalReducedValue = 0;
#pragma omp parallel for reduction(+:finalReducedValue)
for (int64_t i = 0; i < N; ++i) {
    finalReducedValue += ...
}
```

How will we do this with **Kokkos**?

```
double finalReducedValue = 0;
parallel_reduce(N, functor, finalReducedValue);
```

Example: Scalar integration

OpenMP

```
double totalIntegral;
#pragma omp parallel for reduction(+:totalIntegral)
for (int64_t i = 0; i < numberOfIntervals; ++i) {
    totalIntegral += function(...);
}
```

Kokkos

```
double totalIntegral = 0;
parallel_reduce(numberOfIntervals,
    [=] (const int64_t i, double & valueToUpdate) {
        valueToUpdate += function(...);
    },
    totalIntegral);
```

- ▶ The operator takes **two arguments**: a work index and a value to update.
- ▶ The second argument is a **thread-private value** that is managed by Kokkos; it is not the final reduced value.

Warning: Parallelism is NOT free

Dispatching (launching) parallel work has non-negligible cost.

Warning: Parallelism is NOT free

Dispatching (launching) parallel work has non-negligible cost.

Simplistic data-parallel performance model: $\text{Time} = \alpha + \frac{\beta * N}{P}$

- ▶ α = dispatch overhead
- ▶ β = time for a unit of work
- ▶ N = number of units of work
- ▶ P = available concurrency

Warning: Parallelism is NOT free

Dispatching (launching) parallel work has non-negligible cost.

Simplistic data-parallel performance model: $\text{Time} = \alpha + \frac{\beta * N}{P}$


- ▶ α = dispatch overhead
- ▶ β = time for a unit of work
- ▶ N = number of units of work
- ▶ P = available concurrency

$$\text{Speedup} = P \div \left(1 + \frac{\alpha * P}{\beta * N}\right)$$

- ▶ Should have $\alpha * P \ll \beta * N$
- ▶ All runtimes strive to minimize launch overhead α
- ▶ Find more parallelism to increase N
- ▶ Merge (fuse) parallel operations to increase β

Results: illustrates simple speedup model $= P \div \left(1 + \frac{\alpha * P}{\beta * N}\right)$

Kokkos speedup over serial: Scalar Integration



Note: log scale

Always name your kernels!


Giving unique names to each kernel is immensely helpful for debugging and profiling. You will regret it if you don't!

- ▶ Non-nested parallel patterns can take an optional string argument.
- ▶ The label doesn't need to be unique, but it is helpful.
- ▶ Anything convertible to "std::string"
- ▶ Used by profiling and debugging tools (see Profiling Tutorial)

Example:

```
double totalIntegral = 0;
parallel_reduce("Reduction", numberOfIntervals,
    [=] (const int64_t i, double & valueToUpdate) {
        valueToUpdate += function(...);
    },
    totalIntegral);
```

Exercise: Inner product $\langle y, A * x \rangle$



Details:

- ▶ y is $N \times 1$, A is $N \times M$, x is $M \times 1$
- ▶ We'll use this exercise throughout the tutorial

The **first step** in using Kokkos is to include, initialize, and finalize:


```
#include <Kokkos_Core.hpp>
int main(int argc, char* argv[]) {
    /* ... do any necessary setup (e.g., initialize MPI) ... */
    Kokkos::initialize(argc, argv);
    {
        /* ... do computations ... */
    }
    Kokkos::finalize();
    return 0;
}
```

(Optional) Command-line arguments or environment variables:

<code>--kokkos-num-threads=INT</code> or <code>KOKKOS_NUM_THREADS</code>	total number of threads
<code>--kokkos-device-id=INT</code> or <code>KOKKOS_DEVICE_ID</code>	device (GPU) ID to use

Exercise #1: Inner Product, Flat Parallelism on the CPU

Exercise: Inner product $\langle y, A * x \rangle$



Details:

- ▶ Location: Exercises/01/Begin/
- ▶ Look for comments labeled with "EXERCISE"
- ▶ Need to include, initialize, and finalize Kokkos library
- ▶ Parallelize loops with `parallel_for` or `parallel_reduce`
- ▶ Use lambdas instead of functors for computational bodies.
- ▶ For now, this will only use the CPU.

Compiling for CPU

```
cmake -B build_openmp -DKokkos_ENABLE_OPENMP=ON \  
      -DCMAKE_BUILD_TYPE=Release  
cmake --build build_openmp
```


Running on CPU with OpenMP backend

```
# Set OpenMP affinity  
export OMP_NUM_THREADS=8  
export OMP_PROC_BIND=spread OMP_PLACES=threads  
# Print example command line options:  
./build_openmp/01_Exercise -h  
# Run with defaults on CPU  
./build_openmp/01_Exercise  
# Run larger problem  
./build_openmp/01_Exercise -S 26
```

Things to try:

- ▶ Vary problem size with command line argument -S s
- ▶ Vary number of rows with command line argument -N n
- ▶ Num rows = 2^n , num cols = 2^m , total size = $2^s == 2^{n+m}$

<y,Ax> Exercise 01, Fixed Size



More things to try: port your solution to work on the device

- ▶ You will need to update the dynamic memory allocation.
- ▶ Replace `std::malloc` and `std::free` with `Kokkos::kokkos_malloc` and `Kokkos::kokkos_free`.
- ▶ Bonus question: Why does this perform so poorly? (hint: the answer is in this slide deck somewhere)
- ▶ Note that this is just for learning purposes and by no mean a recommended way to manage the lifetime of your arrays. We will see a better way to do this soon.

Compiling for GPU

```
# if the architecture autodetection fails configure with
# -DKokkos_ARCH_VOLTA70=ON for V100
# refer to the documentation for the complete list of supported NVI
# architectures and corresponding flags, or use cmake to discover
cmake -B build-cuda -DKokkos_ENABLE_CUDA=ON
cmake --build build-cuda
```

- ▶ Customizing `parallel_reduce` data type and reduction operator
e.g., minimum, maximum, ...
- ▶ `parallel_scan` pattern for exclusive and inclusive prefix sum
- ▶ Using *tag dispatch* interface to allow non-trivial functors to have multiple “`operator()`” functions.
very useful in large, complex applications

- ▶ **Simple** usage is similar to OpenMP, advanced features are also straightforward
- ▶ Three common **data-parallel patterns** are `parallel_for`, `parallel_reduce`, and `parallel_scan`.
- ▶ A parallel computation is characterized by its **pattern**, **policy**, and **body**.
- ▶ User provides **computational bodies** as functors or lambdas which handle a single work item.

Building Applications with Kokkos

Learning objectives:

- ▶ Integrate Kokkos into your project
- ▶ Build from source
- ▶ Package managers

Building Applications with Kokkos

Learning objectives:

- ▶ Integrate Kokkos into your project
- ▶ Build from source
- ▶ Package managers

Ignore This For Tutorial Only

The following details on options to integrate Kokkos into your build process are NOT necessary to know if you just want to do the tutorial.

- ▶ **Install Kokkos and find it as external package:** For large projects with multiple dependencies installing Kokkos via CMake and then building against it is the best option.
- ▶ **Build Kokkos embedded in your project:** This is an option suited for applications which have few dependencies (and no one depending on them) and want to build Kokkos inline with their application.
- ▶ **Using Spack:** For projects which largely rely on components provided by the Spack package manager.

- ▶ In the spirit of C++ for *code* performance portability, modern CMake aims for *build system* portability
- ▶ Projects that depend on Kokkos should be agnostic to the exact build configuration of Kokkos
- ▶ No CUDA details in C++! No CUDA details in CMake!
- ▶ Kokkos provides a `Kokkos::kokkos` target.
 - ▶ Include directories
 - ▶ Link libraries
 - ▶ Compiler options
 - ▶ Etc
- ▶ Single command in your project should configure all compiler/linker flags:

```
add_library(myLib goTeamVenture.cpp)  
target_link_libraries(myLib PUBLIC Kokkos::kokkos)
```

External Kokkos (recommended for most use cases)

```
cmake_minimum_required(VERSION 3.22)
project(MyProject CXX)

find_package(Kokkos X.Y REQUIRED CONFIG) # Replace X.Y with your minimum required version

add_executable(HelloKokkos HelloKokkos.cpp)
target_link_libraries(HelloKokkos PRIVATE Kokkos::kokkos)
```

See the [Kokkos documentation](#) for the minimum supported compilers and hardware for each release.

How do I control cmake's search procedure?

```
cmake -DKokkos_ROOT=/path/to/kokkos
```

Option 1: via Git Submodules and `add_subdirectory()`

```
git submodule add -b 4.5.01 https://github.com/kokkos/kokkos.git tpls/kokkos
git commit -m 'Adding Kokkos v4.5.1 as a submodule'

add_subdirectory(tpls/kokkos)
target_link_libraries(MyTarget PRIVATE Kokkos::kokkos)
```

Option 2: via FetchContent

```
include(FetchContent)
FetchContent_Declare(
  Kokkos
  URL      https://github.com/kokkos/kokkos/releases/download/4.5.01/kokkos-4.5.01.tar.gz
  URL_HASH SHA256=52d003ffbbe05f30c89966e4009c017efb1662b02b2b73190670d3418719564c
)
FetchContent_MakeAvailable(Kokkos)
target_link_libraries(MyTarget PRIVATE Kokkos::kokkos)
```

Supporting Both External and Embedded Kokkos

```
find_package(Kokkos CONFIG) # Try to find Kokkos externally
if(Kokkos_FOUND)
    message(STATUS "Found external Kokkos")
else()
    message(STATUS "Kokkos not found. Using embedded Kokkos.")
    # or FetchContent if you prefer
    add_subdirectory(tpls/kokkos)
endif()
target_link_libraries(MyTarget PRIVATE Kokkos::kokkos)
```

```
find_package(Kokkos CONFIG) # Try to find Kokkos externally
if(Kokkos_FOUND)
    message(STATUS "Found external Kokkos")
else()
    message(STATUS "Kokkos not found. Using embedded Kokkos.")
    # or FetchContent if you prefer
    add_subdirectory(tpls/kokkos)
endif()
target_link_libraries(MyTarget PRIVATE Kokkos::kokkos)
```

How do I control the Kokkos integration?

```
find_package(Kokkos CONFIG) # Try to find Kokkos externally
if(Kokkos_FOUND)
    message(STATUS "Found external Kokkos")
else()
    message(STATUS "Kokkos not found. Using embedded Kokkos.")
    # or FetchContent if you prefer
    add_subdirectory(tpls/kokkos)
endif()
target_link_libraries(MyTarget PRIVATE Kokkos::kokkos)
```

How do I control the Kokkos integration?

External

```
cmake -DCMAKE_REQUIRE_FIND_PACKAGE_Kokkos=ON -DKokkos_ROOT=/path/to/kokkos
```

Embedded

```
cmake -DCMAKE_DISABLE_FIND_PACKAGE_Kokkos=ON
```

Assert that the (experimental) relaxed constexpr support is enabled

```
if(Kokkos_ENABLE_CUDA)
    kokkos_check(OPTIONS CUDA_CONSTEXPR)
    # fatal error if not enabled
endif()
```

Query whether generation of relocatable device code is enabled

```
kokkos_check(
    OPTIONS CUDA_RELOCATABLE_DEVICE_CODE
    RESULT_VARIABLE KOKKOS_HAS_CUDA_RDC
)
if(NOT KOKKOS_HAS_CUDA_RDC)
    # ...
```

Getting the Kokkos Source Code

Option 1: Downloading a Release Archive (Recommended)

Go to the [Kokkos releases](#) page and find the latest release (or a specific version you need).

```
curl -sLO https://github.com/kokkos/kokkos/releases/download/4.6.01/kokkos-4.6.01.tar.gz
curl -sLO https://github.com/kokkos/kokkos/releases/download/4.6.01/kokkos-4.6.01-SHA-256.txt
grep kokkos-4.6.01.tar.gz kokkos-4.6.01-SHA-256.txt | shasum -c
# the output should be "kokkos-4.6.01.tar.gz: OK" or similar
# if the checksum doesn't match, do not use the archive
tar -xzf kokkos-4.6.01.tar.gz
```

Option 2: Cloning the Git Repository (For Development Versions)

If you need the latest features or want to contribute to Kokkos, you can clone the Git repository.

```
git clone https://github.com/kokkos/kokkos.git
cd kokkos
# checkout a release tag
git checkout 4.6.01
```

Configuring Kokkos

```
cmake -B builddir [<options...>]
```

Common CMake options:

- ▶ `-DCMAKE_CXX_COMPILER=<compiler>` for example `hipcc` for AMD GPUs, `icpx` for Intel GPUs, `nvcc_wrapper` for NVIDIA GPUs
- ▶ `-DCMAKE_CXX_STANDARD=<standard>` default is 17 for Kokkos 4.X, 20 in 5.0
- ▶ `-DCMAKE_BUILD_TYPE=<type>` choose from `Debug`, `Release`, `RelWithDebInfo` (default), and `MinSizeRel`
- ▶ `-DCMAKE_INSTALL_PREFIX=<prefix>`

Important Kokkos-specific options:

- ▶ `-DKokkos_ENABLE_<BACKEND>=ON`
- ▶ `-DKokkos_ARCH_<ARCHITECTURE>=ON`
- ▶ `-DKokkos_ENABLE_DEPRECATED_CODE_4=ON`
- ▶ `-DKokkos_ENABLE_DEPRECATED_WARNINGS=ON`

Refer to <https://kokkos.org> > Documentation > Get Started > Configuration Guide

Backends

- ▶ You can only enable one "device" backend at a time (e.g., CUDA, HIP, or SYCL)
- ▶ Only one "host parallel" backend at a time (e.g., OPENMP or THREADS)
- ▶ A host backend is always required
- ▶ If no host backend is explicitly enabled, the SERIAL backend will be used.

```
-- The project name is: Kokkos
...
-- Execution Spaces:
--   Device Parallel: CUDA
--   Host Parallel: NONE
--   Host Serial: SERIAL
```

Architectures

- ▶ Device architecture is required, Kokkos will try to autodetect it at configuration time if you don't specify anything
- ▶ Host architecture is optional, none by default, you may be able to use
-DKokkos_ARCH_NATIVE=ON

```
-- The project name is: Kokkos
...
-- Architectures:
--   HOPPER90
```

Build

After configuring, build Kokkos using:

```
cmake --build builddir [-j<N>]
```

This compiles Kokkos. You can add `-j<N>` to use multiple cores for faster compilation (replace `<N>` with the number of cores).

Install

To install Kokkos (header files and libraries), use:

```
cmake --install builddir [--prefix <prefix>]
```

The `--prefix <prefix>` option specifies the installation directory. If omitted, Kokkos will be installed to a default location, often `/usr/local` (not recommended).

- ▶ Spack provides a package manager that automatically downloads, configures, and installs package dependencies
- ▶ Kokkos itself can be easily installed with specific variants (+) and compilers (%)

```
spack install kokkos@develop +openmp %gcc@8.3.0
```

- ▶ Good practice is to define “best variant” in your packages.yaml directory, e.g. for Volta system

```
packages:  
  kokkos:  
    variants: +cuda +openmp \  
              ^cuda@12.0 cuda_arch=70  
    compiler: [gcc@8.3.0]
```

- ▶ Build rules in package.py automatically map Spack variants to correct CMake options
- ▶ Run `spack info kokkos` to see full list of variants

- ▶ Build rules created in a `package.py` file
- ▶ Step 1: Declare dependency on specific version of kokkos (4.x or develop)

```
class myLib(CMakePackage):  
    depends_on('kokkos@X.Y') # Replace X.Y with your minimum  
                             required Kokkos version
```

- ▶ Step 2: Add build rule pointing to Spack-installed Kokkos and same C++ compiler Kokkos uses

```
def cmake_args(self):  
    options = []  
    ...  
    options.append('-DCMAKE_CXX_COMPILER={}'.format(  
        self['kokkos'].kokkos_cxx)  
    return options
```

- ▶ More details on <https://kokkos.org> > Documentation > Get Started > Package Managers > Spack

- ▶ Kokkos' primary build system is CMAKE.
- ▶ Kokkos options are transitively passed on, including many necessary compiler options.
- ▶ The Spack package manager does support Kokkos.
- ▶ If you write an application, and have few if any dependencies, building Kokkos as part of your code is an option.

Kokkos Ecosystem:

- ▶ C++ Performance Portability Programming Model.
- ▶ The Kokkos Ecosystem provides capabilities needed for serious code development.
- ▶ Kokkos is supported by multiple National Laboratories with a sizeable dedicated team.

Building Kokkos

- ▶ Kokkos' build system is generated using CMake.
- ▶ Kokkos options are transitively passed on, including many necessary compiler options.
- ▶ The Spack package manager does support Kokkos.

Data Parallelism:

- ▶ Simple things stay simple!
- ▶ You use **parallel patterns** and **execution policies** to execute **computational bodies**
- ▶ Simple parallel loops use the `parallel_for` pattern:

```
parallel_for("Label", N, [=] (int64_t i) {  
    /* loop body */  
});
```

- ▶ Reductions combine contributions from loop iterations

```
int result;  
parallel_reduce("Label", N, [=] (int64_t i, int& lres) {  
    /* loop body */  
    lres += /* something */  
}, result);
```

Kokkos::View:

- ▶ Solving the data-layout issue.
- ▶ Controlling data life-time.

Execution and Memory Spaces:

- ▶ How to control where data lives.
- ▶ How to control where code executes.
- ▶ How to manage data transfers.

Slack channel: <https://kokkosteam.slack.com/>

Recordings/Slides:

<https://kokkos.org/kokkos-core-wiki/videlectures.html>

Sandia National Laboratories is a multi-mission laboratory managed and operated by National Technology and Engineering Solutions of Sandia, LLC., a wholly owned subsidiary of Honeywell International, Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.

SAND2020-7263 PE

The U.S. Department of Energy supported this work through the Los Alamos National Laboratory. Los Alamos National Laboratory is operated by Triad National Security, LLC, for the National Nuclear Security Administration of the U.S. Department of Energy (Contract No. 89233218CNA000001). Approved for public release with LA-UR-26-24642.